

# Infrared Laser Diode

Part No: LD-830-30-50-N-2



## Features

- ※ Wavelength:  $\lambda = 830\text{nm}$  (Type)
- ※ Low threshold current:  $I_{th} = 20\text{mA}$  (Type)
- ※ Output optical power: 30mW
- ※ Package: T0-18 ( $\Phi 5.6\text{mm}$ )

## Applications

- ※ Industrial Use

### Absolute Maximum Rating at $T_c = 25^\circ\text{C}$

Items	Symbols	Values	Unit
Optical Output Power	$P_o$ (CW)	35	mW
	$V_r$ (LD)	2	V
Laser Diode Reverse Voltage	$V_r$ (PD)	30	V
Operating Temperature	$T_{opr}$	$-10 \sim +50$	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	$-40 \sim +80$	$^\circ\text{C}$

### Electrical and Optical Characteristics at $T_c = 25^\circ\text{C}$

Items	Symbols	Min	Type	Max.	Unit	Condition
Optical Output Power	$P_o$	-	30	-	mW	CW
Threshold Current	$I_{th}$	-	20	30	mA	CW
Operating Current	$I_{op}$	-	68	78	mA	$P_o = 30\text{mW}$
Slope Efficiency	SE	0.5	0.6	-	mW/mA	$P_o = 30\text{mW}$
Operating Voltage	$V_{op}$	-	1.7	2	V	$P_o = 30\text{mW}$
Monitor Current	$I_m$	-	0.2	0.8	mA	$P_o = 30\text{mW}$
Lasing Wavelength	$\lambda$	820	830	840	nm	$P_o = 30\text{mW}$
Beam Divergence	//	-	10	-	$^\circ$	$P_o = 30\text{mW}$
	$\perp$	-	35	-	$^\circ$	$P_o = 30\text{mW}$
Beam Angle	$\triangle //$	-	-	$\pm 3$	$^\circ$	$P_o = 30\text{mW}$
	$\triangle \perp$	-	-	$\pm 3$	$^\circ$	$P_o = 30\text{mW}$
Emission Point Accuracy	$\triangle X \triangle Y \triangle Z$	-80	-	80	$\mu\text{m}$	$P_o = 30\text{mW}$

- 1) Measurement condition: CW
- 2) Full angle at half maximum.
- 3) All the above values are measured by OPELUS method.

# Infrared Diode

## Package and Electrical connection

