

Red Laser Diode

Part No: LD-660-2A-60-B-2



Features

- ※ Wavelength: $\lambda = 660\text{nm}$ (Type)
- ※ Low threshold current: $I_{th} = 65\text{mA}$ (Type)
- ※ Output optical power: 200mW
- ※ Package: T0-18 ($\Phi 5.6\text{mm}$)

Applications

- ※ Industrial Use

Absolute Maximum Rating at $T_c = 25^\circ\text{C}$

Items	Symbols	Values	Unit
Optical Output Power	P_o (CW)	200	mW
	P_o (Pulse)	350	mW
Laser Diode Reverse Voltage	V_r	2	V
Operating Temperature	T_{op}	$-10 \sim +60$	$^\circ\text{C}$
Storage Temperature	T_{stg}	$-40 \sim +80$	$^\circ\text{C}$

Electrical and Optical Characteristics at $T_c = 25^\circ\text{C}$

Items	Symbols	Min	Type	Max.	Unit	Condition
Optical Output Power	P_o	-	200	-	mW	CW
Threshold Current	I_{th}	-	65	80	mA	CW
Operating Current	I_{op}	-	280	320	mA	$P_o = 200\text{mW}$
Slope Efficiency	η	0.8	0.95	-	mW/mA	$P_o = 200\text{mW}$
Operating Voltage	V_{op}	-	2.5	3	V	$P_o = 200\text{mW}$
Lasing Wavelength	λ	655	660	665	nm	$P_o = 200\text{mW}$
Beam Divergence	//	8	10	12	$^\circ$	$P_o = 200\text{mW}$
	\perp	15	20	22	$^\circ$	$P_o = 200\text{mW}$
Beam Angle	$\Delta //$	-	-	± 2	$^\circ$	$P_o = 200\text{mW}$
	$\Delta \perp$	-	-	± 2	$^\circ$	$P_o = 200\text{mW}$
Emission Point Accuracy	$\Delta X, \Delta Y, \Delta Z$	-80	-	80		$P_o = 200\text{mW}$

- 1) Measurement condition: CW
- 2) Full angle at half maximum.
- 3) All the above values are measured by OPELUS method.

Red Diode

Package and Electrical connection

